



## PORTABLE SHUNT RESISTOR



### *Serie "Classic"*

For extension of measuring ranges on ammeters HDA and PDA.

This shunt is made in two different constructions:

- 1.) with 4 measuring ranges installed into a plastic case with pressure bolt terminal.
- 2.) with 1 measuring range in self-carrying construction with screw terminal.

### Technical data

**Class of accuracy:** 0,2 acc. to VDE 0410.

**Voltage drop:** 60 mV.

**Weight:** 0,3-1,8 kg.



Dimensions: 202x110x97 mm 6-12-30-60 A  
202x110x97 mm 12-30-60-120 A  
215x55x30 mm 300 A and 600 A  
230x110x65 mm 1200 A

TYPE	Cat. No.	Class of acc.	Measuring ranges	Voltage drop	Dimensions	Mass	Remark
SH	0891-90-002	0.2	1,2-6-12-30A	60 mV	202x110x97 mm	approx. 1.6 kg	in plastic case
	0891-90-001		6-12-30-60A	60 mV	202x110x97 mm	approx. 1.6 kg	
	0891-90-000		12-30-60-120 A	60 mV	202x110x97 mm	approx. 1.6 kg	
	0831-90-000		300 A	60 mV	215x55x50 mm	approx. 0.8 kg	self-carrying layout
	0830-90-000		600 A	60 mV	215x55x50 mm	approx. 2.0 kg	
	0829-90-000		1200 A	60 mV	230x110x65 mm	approx. 2.9 kg	

### **Customers requirement:**

- Portable shunt resistor.
- Range: 600 A

### **Ordering data:**

- Portable shunt resistor.
- Type: **SH**.
- Cat. No. **0830-90-000**.